



US005958057A

United States Patent [19]
Gianni

[11] **Patent Number:** **5,958,057**
[45] **Date of Patent:** **Sep. 28, 1999**

[54] **METHOD AND APPARATUS FOR
POWERING-ON A COMPUTER-BASED
SYSTEM VIA A NETWORK INTERFACE**

[75] **Inventor:** **Robert R. Gianni**, San Jose, Calif.

[73] **Assignee:** **Sun Microsystems, Inc.**, Mountain View, Calif.

[21] **Appl. No.:** **09/152,634**

[22] **Filed:** **Sep. 14, 1998**

Related U.S. Application Data

[63] Continuation of application No. 08/499,085, Jul. 6, 1995, Pat. No. 5,809,313.

[51] **Int. Cl.⁶** **G06F 1/26**

[52] **U.S. Cl.** **713/310; 713/300**

[58] **Field of Search** **395/750.01-750.08, 395/750**

References Cited

U.S. PATENT DOCUMENTS

| | | | |
|-----------|--------|---------------------|---------|
| 4,635,195 | 1/1987 | Jeppesen, II et al. | 395/750 |
| 4,663,539 | 5/1987 | Sharp et al. | 395/750 |
| 4,663,563 | 5/1987 | Sharp et al. | 307/38 |
| 4,677,566 | 6/1987 | Whittaker et al. | 395/750 |
| 4,747,041 | 5/1988 | Engel et al. | 395/750 |
| 5,012,233 | 4/1991 | Paulsen, Jr. | 395/750 |

| | | | |
|-----------|--------|------------------|---------|
| 5,121,500 | 6/1992 | Arlington et al. | 395/750 |
| 5,121,506 | 6/1992 | Arlington et al. | 395/750 |
| 5,381,414 | 1/1995 | Gibson | 395/750 |
| 5,396,636 | 3/1995 | Gallagher et al. | 395/750 |
| 5,535,400 | 7/1996 | Belmont | 395/750 |

FOREIGN PATENT DOCUMENTS

| | | |
|----------|--------|----------------------|
| 92302925 | 4/1992 | European Pat. Off. . |
| 92305570 | 6/1992 | European Pat. Off. . |
| 93304075 | 5/1993 | European Pat. Off. . |

Primary Examiner—Ayaz R. Sheikh

Assistant Examiner—David Wiley

Attorney, Agent, or Firm—Flehr Hohbach Test Albritton & Herbert LLP

[57] **ABSTRACT**

A network interface card in a networked client computer includes a network interface circuit that decodes and then compares incoming network packet addresses to known address bit patterns, the decoding and comparing circuitry being powered at all times. Receipt and recognition of certain addresses means the client computer must be powered-on, even if manually switched OFF. When such a server-transmitted address is recognized, a power-on signal is issued to a power control unit that causes full operating power to be coupled to the client computer. In this fashion, a server can broadcast power-on signals to a plurality of networked client computers or workstations.

20 Claims, 3 Drawing Sheets

